




Bearing de Mexico, S.A.



71906 ACB/P4A Bearing 2D drawings and 3D CAD models

30 mm x 47 mm x 9 mm SKF 71906 ACB/P4A
angular contact ball bearings

Bearing No. 71906 ACB/P4A

Size	47x30x9 mm
Bore Diameter	47 mm
Outer Diameter	30 mm
Width	9 mm
d	30 mm
D	47 mm
B	9 mm
d ₁	35.95 mm
d ₂	35.1 mm
D ₂	43 mm
r _{1,2} - min.	0.3 mm
r _{3,4} - min.	0.15 mm
a	16.5 mm
d _a - min.	32 mm
d _b - min.	32 mm
D _a - max.	45 mm
D _b - max.	46.2 mm
r _a - max.	0.3 mm
r _b - max.	0.15 mm
d _n	36.6 mm
Basic dynamic load rating - C	4.6 kN
Basic static load rating - C ₀	3 kN
Fatigue load limit - P _u	0.127 kN
Limiting speed for grease	36000 r/min



Bearing de Mexico, S.A.

Lubrication	
Limiting speed for oil lubrication	56000 mm/min
Ball - D_w	3.969 mm
Ball - z	22
G_{ref}	0.72 cm ³
Calculation factor - e	0.68
Calculation factor - Y_2	0.87
Calculation factor - Y_0	0.38
Calculation factor - X_2	0.41
Calculation factor - Y_1	0.92
Calculation factor - Y_2	1.41
Calculation factor - Y_0	0.76
Calculation factor - X_2	0.67
Preload class A - G_A	27 N
Preload class B - G_B	54 N
Preload class C - G_C	160 N
Calculation factor - f	1.07
Calculation factor - f_1	0.99
Calculation factor - f_{2A}	1
Calculation factor - f_{2B}	1.02
Calculation factor - f_{2C}	1.07
Calculation factor - f_{HC}	1
Preload class A	53 N/micron
Preload class B	68 N/micron
Preload class C	102 N/micron
d_1	35.95 mm
d_2	35.1 mm
D_2	43 mm
$r_{1,2}$ min.	0.3 mm



Bearing de Mexico, S.A.

$r_{3,4}$ min.	0.15 mm
d_a min.	32 mm
d_b min.	32 mm
D_a max.	45 mm
D_b max.	46.2 mm
r_a max.	0.3 mm
r_b max.	0.15 mm
d_n	36.6 mm
Basic dynamic load rating C	6.05 kN
Basic static load rating C_0	4.9 kN
Fatigue load limit P_u	0.127 kN
Attainable speed for grease lubrication	36000 r/min
Attainable speed for oil-air lubrication	56000 r/min
Ball diameter D_w	3.969 mm
Number of balls z	22
Reference grease quantity G_{ref}	0.72 cm ³
Preload class A G_A	27 N
Static axial stiffness, preload class A	53 N/ μ m
Preload class B G_B	54 N
Static axial stiffness, preload class B	68 N/ μ m
Preload class C G_C	160 N
Static axial stiffness, preload class C	102 N/ μ m
Calculation factor f	1.07
Calculation factor f_1	0.99
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.02
Calculation factor f_{2C}	1.07
Calculation factor f_{HC}	1



Bearing de Mexico, S.A.

Calculation factor e	0.68
Calculation factor (single, tandem) Y_2	0.87
Calculation factor (single, tandem) Y_0	0.38
Calculation factor (single, tandem) X_2	0.41
Calculation factor (back-to-back, face-to-face) Y_1	0.92
Calculation factor (back-to-back, face-to-face) Y_2	1.41
Calculation factor (back-to-back, face-to-face) Y_0	0.76
Calculation factor (back-to-back, face-to-face) X_2	0.67
Mass bearing	0.047 kg